



# HI-COMBAT®

## Ultimate Aggressive Interior Attack Fire Hose

Hi-Combat® is the ultimate in firefighting hose technology for aggressive interior combat operations. Its unique design gives combat firefighters the performance, flexibility, and endurance to deal with the toughest challenges. A special weave, high-tech nylon-polyester outer jacket encases an inner lining consisting of a one-piece, extruded-through-the-weave hose for optimum performance and reliability.

With high-visibility material woven right into the hose, firefighters can follow the "exit" and arrow markings to safety. BullDog can also add up to 32 custom characters sewn into the hose.\* Hi-Combat is available in 5 NFPA colors that are extruded through the weave, not dyed, and will not bleed or wear off. It combines higher heat, abrasion and chemical resistance with unmatched kink resistance and superior ease of drag.

Engineered by BullDog, Hi-Combat is guaranteed to meet specified burst pressure and exceed the NFPA 1961 standard. Hi-Combat's super powerful attributes set standards for fire hose that every firefighter deserves.

*\*Available on 1-3/4" and 2" only. 1000' minimum order requirement.*

### UNIQUE DESIGN FEATURES:

- Colors are extruded through the weave, not dyed, and will not bleed or wear off
- High-visibility safety material
- Available in 5 NFPA colors
- High abrasion resistance
- High heat resistance

**Backed by BullDog's Municipal  
Fire Hose Ten-Year Warranty.**  
[bulldoghose.com/resources](http://bulldoghose.com/resources)



**Raise your firefighting standards!**

Contact us today: 712.655.9201 · [bulldoghose.com](http://bulldoghose.com)

**AMERICAN MADE TOUGH.™**

## FEATURES:

**Designed for Aggressive Interior Combat Operations**

**Minimized Friction Loss**

**Excellent Kink Resistance**  
Kink resistance exceeds that of conventional jacketed hose.

**Superior Abrasion Performance**  
Abrasion-resistant outer jacket is designed and manufactured to withstand a minimum of 2,000 cycles on the U.L. abrasion test and 12,000 cycles on the F.M. abrasion test programs.

**Lowest Drag Coefficiency**  
Drag coefficient is the lowest of any fire hose BullDog has tested, making it easier to advance during attack operations.

**Ideal for Personal Portable Monitors and High-Rise Firefighting Operations**

**Anti-Burst Technology**  
Ensures it will not burst catastrophically — even with a 1/2" diameter hole through both the jacket and liner.

**Exceeds Standards**

Hi-Combat® is manufactured to meet or exceed the NFPA 1961 standard.

**Chemical-Resistant Liner**  
Protects from exposure to water and contamination by most chemical substances, hydrocarbons, oil and grease.

**Temperature range -36°F to +158°F**

**ULC**  
Available on 1-3/4" and 2-1/2".

## TECHNICAL SPECIFICATIONS:

Size	Pressure						Bowl Size	Weight (50'/15M)	Coil Diameter (50'/15M)
	Service	Proof	Burst						
inch mm	psi kpa	psi kpa	psi kpa			inch	lbs kg	inch mm	
1-3/4 45 ULC	500 3,500	1,000 7,000	1,500 10,500			2-1/8	18 8.10	16.5 419	
2 50	500 3,500	1,000 7,000	1,500 10,500			2-3/8	20 9.07	17.5 445	
2-1/2 65 ULC	500 3,500	1,000 7,000	1,500 10,500			2-7/8	23 10.4	18.5 470	

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.



**HIGH-VISIBILITY EXIT ARROWS PROVIDE ADDED SAFETY THROUGHOUT ENTIRE HOSE**

**32 CUSTOM CHARACTERS ALLOWS THE DEPARTMENT NAME TO BE WOVEN INTO THE HOSE\***

**YOUR NAME HERE**

*\*Available on 1-3/4" and 2" only. 1000' minimum order requirement.*

