Product leaflet

Product	Model No.	Ordering No.
Compressed air filter	SR 99-1	H03-2810

Product Description

The SR 99-1 compressed air filter is used for producing clean breathing air from ordinary compressed air.
The unit consists of a regulator (C), pre-collector (D) and main filter (SR 292), all of which are mounted in an enclosing steel sheet stand. The unit can be placed on the floor or mounted on a wall.
The pre-separator has automatic drainage, separates coarser particles, water and oil.
The SR 292 main filter consists of a carbon filter part, surrounded by two P100 particulate filters. The air is cleaned to remove any remaining particles/gases/vapours/odours.
A Y coupling that increases the number of outlets is available as accessory.

Technical specification

	SR 99-1
Inlet connection	1/2" BSP
Inlet pressure	87-145 PSI (6-10 bar)
Outlet connections	One safety coupling and one plugged opening
Flow rate	≈ 32 CFM (900 l/min)
Filter area P100	≈ 2,600 cm²
Activated carbon	≈ 1.1 lbs (500 g)

A. Pressure gauge
B. Inlet
C. Regulating valve
D. Pre-collector
E. Drain
F. Outlet
G. Particulate filter
H. Activated carbon



Sundstrom Safety Inc.
143 Maple St.
Warwick, RI 02888

Office: 1-401-434-7300
Toll Free: 1-877-SUNDSTROM
Fax: 1-401-434-8300
info@srsafety.com
www.srsafety.com

P03H-2821 Rev 02 20220518

Sundström
www.srsafety.com