

LEVEL 1

dusk



RoHS COMPLIANT CE

Dusk

710-401 (110v)
710-404 (230V)

Features

- 1000 watt extruded aluminum heat exchanger
- Continuous fog output with auto-ramping
- Simple On/Off control switch
- Rear mounted for virtually maintenance free operations (regular cleaning only)

Specifications

Output: 1L/h of Smoke Fluid
Power: 9.1A @ 110V/60 Hz
4.3A @ 230V/50Hz
Weight: 11.9 lbs
Dimensions: 16.0 x 7.5 x 8.2 inch
Houseing: Rugged 12 gauge steel case
Chip resistant powder-coated paint
Hard point attachments for hanging
Approvals: CE
RoHS Compliant
ETL / cETL (Pending)
Warranty: 1 Year

SHADOW

SMOKE MACHINES

LEVEL 2

NIGHTFALL



RoHS COMPLIANT CE

Nightfall

710-430 (110v)
710-435 (230v)

Features

- 1200 watt heat exchanger
- 7 Minute start-up time
- Direct thermal protection
- Rear mounted XLR socket (provides 12V DC at 50mA) to power and interface device for triggering the machine. (eg. remote control).
- Removable digital remote control with 9.8 foot cable
- Adjustable flow rate
- Permanent heating system
- Programmable emission



Specifications

Output: 21,190 ft³/min Flowrate in continuous low-flowrate operation
Power: 1050W, 8.75A @ 110V 60 Hz
Weight: 24.7 lbs
Capacity of built-in tank: 0.66 Gallon/2.5 liters
Fluid consumption: 0.02 Gal/min
Dimensions: 19.1 x 13.2 x 9.6 inch
Warranty: 5 Years

LEVEL 3

BLACKOUT



RoHS COMPLIANT CE

Blackout

710-431 (110v)
710-436 (230v)

Features

- 2100 watt heat exchanger
- 10 Minute start-up time
- Direct thermal protection
- Rear mounted XLR socket (provides 12V DC at 50mA) to power and interface device for triggering the machine. (eg. remote control).
- Removable digital remote control with 9.8 foot cable
- Adjustable flow rate
- Permanent heating system
- Programmable emission



Specifications

Output: 46,615 ft³/min Flowrate in continuous low-flowrate operation
Power: 1800W, 15A @ 110V 60 Hz
Weight: 39.1 lbs
Capacity of built-in tank: 1.32 Gallon/5 liters
Fluid consumption: 0.05 Gal/min
Dimensions: 23.1 x 15.6 x 12.1 inch
Warranty: 5 Years