

The Survivor features a low-profile bezel that doesn't interfere with gear and equipment. A reinforced D-ring provides forward-hanging orientation. Safety-rated for Class I, Div. 1 environments.



**Low-profile design doesn't interfere with gear and equipment**

Rubber dome push-button switch easy to use with gloves

Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation

Interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

Rugged nylon polymer body is virtually indestructible

Specialized optic combines low profile with strong performance and a wide beam

**DUAL POWER SOURCE:**  
Rechargeable NiMH battery also accepts (4) "AA" alkaline batteries

No tools needed to change batteries

High, low, emergency flash and moonlight modes:

- High for a super-bright, smoke piercing beam: 175 lumens; 405m beam distance; runs 3.5 hours (NiMH); runs 4 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 13 hours (NiMH); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 20 days

Optimized electronics provide regulated intensity

Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel

IPX4-rated; water-resistant; 2m impact resistance tested

7.06 in. (17.92 cm); NiMH: 18 oz. (510g); Alkaline: 13.7 oz. (388g)

Class I & II, Division 1, Groups C, D, E, F, G, Class III, T-Code: T4; Class I, Division 2, Groups A, B, C, D, T-Code: T4

Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

Limited Lifetime Warranty  
Visit [streamlight.com](http://streamlight.com) for full warranty information

ORANGE	YELLOW	BLACK	DESCRIPTION
90505	90515	90525	Survivor - 230V AC/12V DC
90506	90516	90526	Survivor - 240V AC/12V DC
90503	90513	90523	Survivor - 120V AC/12V DC
90500	90510	90520	Survivor - without charger
90540	90541	90545	Survivor - alkaline