



SURVIVOR[®]



SAFETY-RATED, RIGHT-ANGLE FLASHLIGHT



Custom designed optic with optional, interchangeable Smoke-Cutter[®] plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

Available Colors: 

The Survivor features a low-profile bezel that doesn't interfere with gear and equipment. A reinforced D-ring provides forward-hanging orientation. Safety-rated for Class I, Div. 1 environments.

KEY FEATURES

- Rubber dome push-button switch, easy to use with gloves
- Super strong, spring-loaded gear clip securely grabs onto turnout gear
- Specialized optic combines low profile with strong performance and a wide beam

OUTPUT

	HIGH	LOW
LUMENS	175	60
CANDELA	41,000	14,000
DISTANCE	405m	237m
RUN TIME _{NiMH}	3.5 hrs	13 hrs
RUN TIME _{Alkaline}	4 hrs	15 hrs

Flash for signaling: runs 8 hrs

Moonlight mode provides low-level lighting for battery conservation: runs 20 days

ITEM NUMBERS

Description	UPC	Item #
Survivor - 120V/100V AC/12V DC - Yellow	080926-90513-9	90513
Survivor - 120V/100V AC/12V DC - Black	080926-90523-8	90523
Survivor - 120V/100V AC/12V DC - Orange	080926-90503-0	90503

see reverse side for additional item numbers

BATTERY

- NiMH 4.8V, 2.6Ahr, 4 cell sub-C rechargeable up to 1,000 times
- Optional (4) AA alkaline batteries (requires battery carrier)
- No tools needed to replace batteries

MATERIAL/DURABILITY

- Housing, base, and battery made from high-impact, rugged nylon polymer body which is virtually indestructible
- Unbreakable polycarbonate lens with silicone anti-scratch coating
- One-way valve for case venting
- IPX4-rated; water-resistant; 2m impact resistance tested

DIMENSIONS

W x H: 2.85 x 7.06 in (7.24 x 17.9 cm)

WEIGHT: NiMH 18.0 oz (510g) // ALKALINE 13.7 oz (388g)

SAFETY RATINGS

- Class I, II, Division 1, Groups C, D, E, F, G; Class III, T-Code: T4
- Class I, Division 2, Groups A, B, C, D; T-Code: T4
- Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- MSHA: Permissible Flashlight, Approval No. 20-A150001-0

WARRANTY

Limited lifetime warranty

Visit streamlight.com for full warranty information

ITEM NUMBERS

Description	UPC	Item #
Survivor - 230V AC/12V DC - Yellow	080926-90515-3	90515
Survivor - 230V AC/12V DC - Black	080926-90525-2	90525
Survivor - 230V AC/12V DC - Orange	080926-90505-4	90505
Survivor - 240V AC/12V DC - Yellow	080926-90516-0	90516
Survivor - 240V AC/12V DC - Black	080926-90526-9	90526
Survivor - 240V AC/12V DC - Orange	080926-90506-1	90506

Description	UPC	Item #
Survivor - Without Charger - Yellow	080926-90510-8	90510
Survivor - Without Charger - Black	080926-90520-7	90520
Survivor - Without Charger - Orange	080926-90500-9	90500
Survivor - Alkaline - Yellow	080926-90541-2	90541
Survivor - Alkaline - Black	080926-90545-0	90545
Survivor - Alkaline - Orange	080926-90540-5	90540

ACCESSORIES

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger 5-Unit 230V AC Bank Charger 5-Unit 12V DC Bank Charger	080926-90910-6 080926-90911-3 080926-90912-0	90910 90911 90912
	Battery Carrier (for alkaline models) <i>Batteries not included</i>	080926-90542-9	90542
	Charger Holder	080926-90345-6	90345
	NiMH Battery Pack	080926-90339-5	90339
	240V AC (AUS/NZ) Charge Cord	080926-22048-5	22048
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V UK AC Charge Cord	080926-22062-1	22062
	Smoke Cutter Plug Kit	--	908019