

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.  
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.  
 Download the instructions at [PETZL.COM](http://PETZL.COM).



# EVACUATION TRIANGLES

## User information

Surname

Address

Identifier

## PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Crolles - France

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	N/A Not applicable

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	N/A
----------------------------------	-----------------------	-----------------------	-----------------------	-----------------------	-----

### 2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 3. Checking the condition of the straps

- Check the condition of the straps (cuts, swelling, damage and wear due to use, to heat, to contact with chemicals...). Check the waist straps, thigh straps, crotch and shoulder straps, if present. Be sure to check the areas hidden by the buckles and attachment points.
- Check the condition of the safety stitching on both sides. Look for any threads that are loose, worn, or cut. Safety stitching is identified by thread of a different color than that of the webbing.
- Verify that hems are present on the strap ends.

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 4. Checking the attachment points

- Check the condition of the metal attachment points (marks, cracks, wear, deformation, corrosion...).

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 5. Checking the condition of the adjustment buckles

- Check the condition of the DOUBLEBACK adjustment buckles (marks, cracks, wear, deformation, corrosion...).
- On THALES, check the condition of the FAST LT adjustment buckle (marks, cracks, wear, deformation, corrosion...).
- Check that the straps are correctly threaded, with no twists.
- Verify that the buckles operate properly.

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 6. Checking the condition of the comfort parts

- Check the condition of the seat (cuts, wear, tears...).
- Check the condition of the elastic and/or plastic keepers (cuts, wear, tears...).
- If applicable, check the condition of the dorsal guide handle (cuts, wear, tears...).

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### 7. Checking the condition of the closing connector (if any)

- Verify that the connector is the correct model and that it is correctly attached to the harness.
- For connector inspection, see the inspection form for your connector model at [PETZL.COM](http://PETZL.COM)

<input type="radio"/>				
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

### Comments (detail here any defects found on the product and accomplished tasks)

### VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date  Next inspection date