

E-FLOOD® LITEBOX® // E-FLOOD® FIREBOX®
RECHARGEABLE LED LANTERN

DESCRIPTION: The E-Flood® LiteBox® and FireBox® deliver 1,500 lumens and 4,700 candela of diffused light. The lithium-ion battery provides enhanced performance in a lightweight device. The large tactile push-button switch (with built-in battery status indicator) and a large grip area make this lantern easy to use, even with gloved hands. This light is also easy to carry, whether it's by hand or with the heavy-duty shoulder strap. The articulating head and ability to stand the light upright allows the user to aim light right where it's needed. The E-Flood® models use four (4) LEDs with shallow reflectors for a widened beam pattern. The LiteBox® is also available in a Power Failure version.

CASE MATERIAL: High-impact ABS thermoplastic.

DIMENSIONS: Length: 11.2 in (28.4 cm) Width: 5.0 in (12.7 cm) Height: 6.4 in (16.3 cm)

WEIGHT: 3.1 lbs. (1389 g)

LENS: Unbreakable polycarbonate with scratch-resistant coating.

LIGHT SOURCE: Four (4) high-power LEDs, impervious to shock with a 50,000-hour lifetime. Two (2) ultra-bright blue taillight LEDs (FireBox® models only).

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity.

ON/OFF: Push-button with integrated battery charge indicator. Press and hold to cycle through the different modes.

RUN TIME: See chart.

BATTERY: Lithium-ion 7.4V, 5200 mAh with onboard safety control, rechargeable up to 500 times. Recharges in 5 hours with provided power supplies. Red and green LEDs in the push-button indicate battery status. When operating, flashing red indicates charging is needed. When charging, green indicates fully charged.

FEATURES: Cool white LED technology for extreme brightness.
 IPX4-rated design.
 1-meter impact resistance tested.
 Serialized for positive identification.



Models: Available in international safety orange or high-visibility yellow.

Vehicle Mount E-Flood LiteBox System: Includes shoulder strap and vehicle-mountable hard-wired rack.




Vehicle Mount E-Flood FireBox System: Vehicle Mount E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs.

Standard E-Flood LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack.





Standard E-Flood FireBox System: Standard E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs.

Power Failure E-Flood LiteBox System: Includes shoulder strap, AC and DC charge cords, and charge rack plus "smart" power failure circuitry that automatically turns the lantern on when the power goes off.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:  Meets applicable United Kingdom and European Community Directives.
 Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.
 CEC Compliant.

OPTIONAL ACCESSORIES: 100V, 120V, 230V, or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap (included with standard + VM models), locking charge rack, quick-release shoulder/waist strap

	FL 1 Standard	HIGH	LOW
OUTPUT	 1500 LUMENS	1500 LUMENS	350 LUMENS
RUN TIME	 7h 30min	7h 30min	17h 45min
DISTANCE	 137m	137m	63m
INTENSITY	 4,700cd	4,700cd	1,000cd