

PROTAC® 2AA-X USB
MULTI-FUEL, PERSONAL CARRY TACTICAL FLASHLIGHT

DESCRIPTION: Producing 550 lumens and 10,250 candela, the ProTac® 2AA-X USB flashlight uses Streamlight's proprietary protected lithium polymer USB-C rechargeable battery pack. It also accepts two (2) AA disposable batteries creating 270 lumens and 5,000 candela. This light features a tail cap switch for momentary or constant on operation and three different user-selectable programs.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in black or coyote.

DIMENSIONS: Length: 6 in (15.3 cm) Head diameter: 0.9 in (2.3 cm) Body Diameter: 0.7 in (1.8 cm)

WEIGHT: 3.5 oz (99 g) with either battery type.

LENS: Glass lens. Gasket-sealed.

LIGHT SOURCE: LED technology, impervious to shock with a 50,000-hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

ON/OFF: Multi-function, push-button tail switch. One-handed operation of momentary, variable intensity, or strobe modes. TEN-TAP® programmable switch allows for user selection of one of three different programs: high/strobe/low (factory default), high only, or low/high.

RUN TIME: See chart for specific battery type. All claims are to 10% of initial lumen output.

BATTERY: One (1) Streamlight proprietary protected lithium polymer USB-C rechargeable battery pack with on-board safety control, 1600mAh, rechargeable up to 500 times. Recharges in 4 hours. Also accepts two (2) AA alkaline batteries.

FEATURES:



LED technology for extreme brightness.
 IPX7-rated design; waterproof to 1 meter.
 2-meter impact resistance tested.
 Multi fuel; accepts proprietary lithium polymer or AA batteries.
 TEN-TAP® programmable switch allows user to select one of three different programs.
 Anti-roll face cap.
 Serialized for positive identification.
 Removable pocket clip and holster.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:  Meets applicable United Kingdom and European Community Directives.
 CEC Compliant (with rechargeable battery pack only).

OPTIONAL ACCESSORIES: Holster, charge cord

	Lithium Polymer Battery			AA Batteries			
	FL 1 Standard	HIGH	LOW	FL 1 Standard	HIGH	LOW	
OUTPUT		550 LUMENS	40 LUMENS		270 LUMENS	18 LUMENS	
RUN TIME		2h 15min	16h		2h 30min	48h	
DISTANCE		203m	54m		141m	40m	
INTENSITY		10,250cd	740cd		5,000cd	400cd	
		Strobe Run Time: 4 hrs. 30 min				Strobe Run Time: 5 hrs.	