

The E-Flood LiteBox produces diffused light over an entire area using four LEDs with shallow reflectors for a widened beam pattern. An articulating head allows you to aim light where it is needed. Its large push-button switch is easy to use with heavy gloves and a large grip area makes for easy hand-offs.



Flat side allows light to tilt and stand on its own to light up a scene



Handle clearance accommodates heavy gloves, making hand-offs easier



Multi-function, push-button switch features battery status indicator

Four high-power LEDs produce a wide flood beam pattern; optimized electronics provide regulated intensity
Two levels of lighting: – High: 1,500 lumens; 137m beam; runs 7 hours 30 minutes – Low: 350 lumens; 63m beam; runs 17 hours 45 minutes
Standard System – International safety orange or high visibility yellow; includes shoulder strap, AC and DC charge cords, and mounting rack.
Vehicle Mount System – International safety orange or high visibility yellow; includes vehicle-mountable hard-wired rack and shoulder strap.
Power Failure System – International safety orange; includes AC and DC charge cords and “smart” power failure circuitry which automatically illuminates the E-Flood LiteBox when the power goes out.
IPX4-rated; water-resistant

11.2 in (28.4 cm); 3.1 lbs. (1389 g)		
Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position		
Limited Lifetime Warranty Visit streamlight.com for full warranty information		
E-FLOOD LITEBOX	ORANGE	YELLOW
Standard System - 230V AC/12V DC	45802	45822
Standard System - 240V AC/12V DC	45803	45823
Standard System - 120V AC/12V DC	45801	45821
Vehicle Mount System - 12V DC	45805	45825
Power Failure System - 230V AC/12V DC	45808	---
Power Failure System - 120V AC/12V DC	45807	---
LiteBox Only (without charger)	45806	45826