

FSI F-ECC75WH 3 gpm and F-ECC150WH 6 gpm



Propane tank not included

The **F-ECC150WH** Water Heating System replaces the F-Z100WH, and is a portable wheeled, 150,000+ BTU propane powered unit (propane tank not included), 65 LBS./30Kg w. cart. 10" D X 16" W X 40" H (25 X 40 X 101 cm), approx. Approx. 6.0 gpm/360 gallons per hour (24 lpm/1,440 lph) of heated water FSI does not recommend for use with other than the smaller DAT® series showers such as the DAT®1010S/2020S/2525S/2626S.

For larger FSI FDAT® series units FSI recommends multiple **F-ECC150WH** units or the purchase of the larger capacity FSI Heat 200 water heater. Complete with Anti-freeze sensors. ¾" gas and water fittings w. shut offs included. Comes with 110/120-volt UL power cord powering the internal exhaust fan/digital display – only pulls 12 amps during use. Temperature rise of 38 degrees F. CSA certified for installation in the US and Canada. Meets and exceeds all safety/efficiency requirements of DOE – Energy Factor Rating of .83. Functional to 5,000' elevation.

The **F-ECC75WH** is a liquid propane, portable wheeled, 3 gpm/180 GPH (12 liters/720 mph), 75,000 BTU tankless water heater unit complete; includes an electronic ignition powered by 2 "D" cell batteries; ideal operating range 20~80 PSI; may also be used with modified water systems such as a 12-volt pump; approx. 48 lbs./22 Kg w. cart, adjustable temperature controls, 13" L X 15" W X 40" H/33 X 38 X 101 cm; 20 Minute automatic safety shutoff timer; includes 1 cart - 1 Stainless steel rain cap - 1 Garden hose adapter - 1 CSA regulator for use with standard 20-pound (lb.) propane tank - 1 Chrome shower head w. stainless steel hose; Energy Factor rating 79%; Rated heat input: 20kw; Rated gas pressure: 11" of water column; Drain and store when not in use; Functional to 5,000' elevation; Can increase water temp. by approx. 38 degrees; ¾" gas and water fittings w. Shut offs included; Water heater alone is 17.5 lbs and 15" W X 35" L X 6.5" D. .

